

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number  
**WO 2004/022281 A1**

(51) International Patent Classification<sup>7</sup>: **B23P 19/06 //**  
F16B 37/04

(21) International Application Number:  
PCT/SE2002/001580

(22) International Filing Date:  
5 September 2002 (05.09.2002)

(25) Filing Language: Swedish

(26) Publication Language: English

(71) Applicant and

(72) Inventor: EICSSON, Christer [SE/SE]; Måsvägen 4,  
SE-294 76 Sölvesborg (SE).

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,  
VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,  
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

(74) Agent: AWAPATENT AB; Box 5117, SE-200 71 Malmö  
(SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: TOOL FOR PIERCING NUT



(57) Abstract: The invention relates to a tool for piercing nuts, comprising a die part and a punch part and a piercing nut feeder incorporated into the punch part. The piercing nut feeder is adapted to feed piercing nuts into a piercing nut holder in the punch part so that these nuts, when the punch part is pressed against the die part by a press, are to punch holes in and be fastened to a metal sheet inserted between the punch part and the die part. A gas spring (3) is arranged between the press and the punch part, which gas spring (3) has at least one cylinder (5-7) and a piston (8-10) which is movably arranged in the cylinder (5-7) and which is aligned with the press, the pressure in the cylinder (5-7) being settable for adjusting the pressure exerted upon the piercing nut by the punch part.

WO 2004/022281 A1